

RYETEC PROFESSIONAL HD FLAIL MOWER

FRONT & REAR MOUNTED

The Professional range offers a robust frame and rotor combination with a range of flail options. They can operate in most conditions, both long and overgrown grass and light scrub (up to 35mm thick) to fine finish lawns leaving a smart rolled finish. The heavy duty transmission with oil immersed cross shaft and remote greasing points allows for easy maintenance and a long trouble free working life. The optional front mounted castor wheels give accurate cutting height control and reduce the possibility of scalping (recomended).

Standard Specification:

- » 1.6m, 1.8m & 2.0m models available
- » 5mm Y flail or 0.6kg hammer flail option cut through scrub up to 35mm
- » Tripple V belt drive to the rotor
- » Full width height adjustable rear roller able to leave a striped finish

» Heavy duty frame construction. » 540rpm PT0 » Front or rear mounted (dual linkage)

Options: (recomended in bold)

- » Front mounted caster wheels to follow the ground contours
- » HD side skids
- » Hydraulic side shift

Model	Cutting width (m)	Weight (kg)	Number of flails	Min. tractor hp
P1600HD (Y Flail)	1.6	340	96	35
P1800HD (Y Flail)	1.8	410	116	45
P2000HD (Y Flail)	2.0	463	128	55
P1600HD (Hammer)	1.6	370	20	40
P1800HD (Hammer)	1.8	435	24	50





